

Name	DeoAdd V 300	
Description	EP-/AW-AO/-Additive	
Active substance	Organic Sulphur Compound	
Appearance	light brown, clear liquid	
Analytical values		
Total Sulfur (%)	ASTM D 1552 (LECO)	29.0 - 32.0
Kinematic viscosity at 40 °C (mm/s)	DIN EN ISO 3104	340 - 400
Kinematic viscosity at 100 °C (mm/s)	DIN EN ISO 3104	10 - 20
Density at 25°C (g/cm ³)	DIN EN ISO 12185	1.04 - 1.08
Flashpoint (°C)	DIN ISO 2592	>180
Treat Rate (%)	0.5 - 5.0	
Supply Form	200 kg in steel-drums	
Storage Stability		
In originally sealed package in dry places at max. 25 °C	min. 1 year	

Application

DeoAdd V 300 is a multifunctional ashless additive which can be used as an extreme pressure, antiwear and antioxidant additive.

DeoAdd V 300 is ideally suited for formulating ashless lubricants and greases.

DeoAdd V 300 is soluble in most base oils, but it is recommended to test the solubility, since base oils may differ from supplier to supplier.

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party's rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client's exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.

Valid 18th February 2009