

<b>Name</b>	<b>DeoAdd MRD 10</b>	
<b>Description</b>	EP additive	
<b>Composition</b>	sulphurized fatty acid ester	
<b>Appearance</b>	light brown clear liquid	
<b>Analytical values</b>		
Sulphur (%)	ASTM D 1552 (LECO)	9.0 - 11.0
Kinematic viscosity at 40 °C (mm <sup>2</sup> /s)	DIN EN ISO 3104	240 - 280
Density at 15°C (g/cm <sup>3</sup> )	DIN EN ISO 12185	0.955 - 0.995
Copper corrosion 10% in paraffin Oil 3 h at 100 °C	DIN EN ISO 2160	max. 1b
<b>Treat Rate</b>	5 - 15 %	
<b>Supply Form</b>	200 kg in Steel-Drums	
<b>Shelf Life</b>		
In originally sealed package at room temperature	at least 12 months	

## **Application**

EP additive for metal working fluids. For drilling and cutting oil.  
DeoAdd MRD 10 is an inactive product and therefore particularly suitable for non-ferrous metal working fluids.  
To increase performance a combination with fatty oils is recommended.

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party's rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client's exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.

Valid 13.01.2006