

Name	Deogrip WPF
Description	Softtouch additive, antislip additive
Composition	radically cross-linked, modified castor oil
Appearance	white, finely ground product
Analytical values	
Ash, 2h at 950°C [%] DIN EN ISO 3451-1	max. 0,2
Particle size d ₅₀ [µm] ISO 13320	approx. 120
Particle size d ₉₀ [µm] ISO 13320	approx. 500
Density at 25°C [g/cm ³] DIN ISO 787 T10A	0.98 – 1.02
Supply Form	25 kg in PE-bags
Classification and Labelling	Not necessary
Storage Stability	
in originally sealed package in cool and dry places	min. 1 year

Behaviour and Effects

Softtouch additive and anti-slip agent for coating systems.

Deogrip WPF can be used in thick film protective industrial coatings to obtain a degree of anti-slip properties. Due to its particle size in standard or thin film coatings, an intensive pre-grinding of the material is necessary.

For thin film coatings we would like to refer to our product line Deogrip Micro.

Typical dosage ranges from 5 to 15 %, but can deviate in single cases. Due to the usage of Deogrip WPF it is possible to reach exceptional effects on the surface.

Due to its viscoelastic properties, Deogrip WPF offers the possibility for shock-absorbing effects.

Deogrip WPF is based on sustainable raw material (Castor Oil).

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party's rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client's exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.

Valid 15th January 2015