名稱	**Deovulc EG 3 MF**
描述	複合促進劑
組成	高活性促進劑的協同組合，不含ETU
外觀	米色，無塵粉末

分析值

總硫 [%]	DIN 51724-3	30.5 - 33.5
密度 at 20 °C [g/cm³]	DIN ISO 787 part 10 A	大約 1.43

劑量

推薦 [phr]	3 - 5
硫磺[phr]	0.75 – 1.75, 最好是 1.0
額外促進劑	not required

德國食品法規 (BfR recommendation XXI) 未受批准

美國聯邦法規, FDA - CFR Title 21, Part 177.2600 不在列表中

供應形式 20公斤，聚乙烯內袋並裝在紙箱內

儲存穩定性

在原始包裝且室溫乾燥下 最少 18 個月

分類與標籤

詳細資訊請參考安全資料表。

行為與效果

Deovulc EG 3 MF是一種快速硫化的EPDM一級複合促進劑，不產生噴霜、殘色。

Deovulc EG 3 MF取代了EPDM中複雜的促進劑組合，具有良好的耐熱性和低壓縮永久變形。

Deovulc EG 3 MF適用於所有常見的加工技術，如擠出或射出成型。

根據REACH的規定，Deovulc EG 3 MF不含任何SVHC或CMR物質，但提供了與我們成熟的複合促進劑Deovulc EG 3相似的硫化特性。

*由於橡膠成分多元，故我們不能保證所有的應用都不會噴霜。

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party´s rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client´s exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.

Valid from