

# EP-0415

## Refined soybean oil

**Packing** : 180 kg / iron drum.

**Ingredients** : Soybean oil.

**Application** : The product can effectively ensure that the flexibility of the synthetic rubber is not affected by temperature changes, and easy to mix with Silicon dioxide. It also helps to increase production efficiency and reduce energy consumption.

**Storage** : The product should be stored in the dry and cooling place with good ventilation. Avoiding exposure of the packaged product to direct sunlight. The validity is 1 year.

Items	Standard	Method	Units
Color	below R1.5Y15	CNS3641	Means of lovibond tintometer
Moisture content	below 0.1	CNS3642	%m/m
Impurity content	below 0.05	CNS3643	%m/m
Specific gravity	0.919-0.925	CNS3644	20°C/20°C
Index of refraction	1.466-1.470	CNS3645	nD40°C
Iodine value	124-139	CNS3646	
Acid value	below 0.15	CNS3647	mg KOH/g Oil
Saponification value	189-195	CNS3648	mg KOH/g Oil
Unsaponifiable matter	below 1.0	CNS3649	%
Peroxide value	below 3	CNS3650	meq O <sub>2</sub> /kg Oil
Cooling test	Clarified after 5.5 hours	CNS3652	

1. The product complies with the CNS-749-N5009 National Standard.
2. The value of heavy metal, erucic acid, aflatoxin, total polar compounds, benzo pyrene comply with food safety and hygiene management regulatory requirements.
3. This specification complies with the quality standard. The acid value and peroxide value of the oil will increase with the storage time and ambient temperature.

**ANYKING INTL TRADING CO.,LTD**

18F-1, No.128, Chungde Rd., Sec. 2, Taichung City 406, Taiwan, R.O.C

TEL:04-22381380 FAX:04-22381379

WWW.ANYKING.COM.TW